LIFESAVER®

Quick User Guide

INSTRUCTIONS

This quick user guide should be used in conjuction with the Instruction Manual provided with your LIFESAVER® cube™.

The full technical instruction booklet can be found online at www.lifesaversystems.com.

FIRST USE

1. **Priming** - Unscrew and remove the pump from the LIFESAVER® cube™. Fill with tap water, camp water or water from any clean source to the top. Screw pump firmly back into place. Let stand for 5-10 minutes.

2. **Pump & Discard** - Turn the tap to the open position. Pump several times until water starts to flow. Empty cube™ through tap, do not drink. Repeat twice. Your LIFESAVER® cube is ready to use.

ROUTINE USE

1. **Caution!** - When filling the LIFESAVER® cube™ with water take care to keep the tap area clean.

2. **Filling** - Unscrew and remove pump. Fill with water from tap, camp, river, lake, stream or other source to the top. Use the cleanest water source available. This will prolong the life of your LIFESAVER® cube™.

3. **Pumping** - Ensure tap is closed and pump a few times.

4. **Drinking** - Push tap cap down and turn tap cap to open position or twist and lock tap cap to enable clean, sterile drinking water to flow. Continue to pump to improve flow. Turn tap off after use.

5. **Operation & Storage** - Your LIFESAVER® cube™ will work in different orientations. As the water gets low changing the orientations will improve the flow rate. Protect from freezing and shocks.

IMPORTANT

- Ensure the product is always kept full of water once primed
- Do not drop or subject to shock
- Be careful not to over pump & over pressurise this product



© 2007-2013 LIFESAVER® systems ltd. All rights reserved. Patents and registered designs pending and granted. LIFESAVER® is a registered trade mark. The following are trademarks of the LIFESAVER® group of companies:- FOR A HOSTILE WORLD™, FILL.PUMP.DRINK™, FAILSAFE™

V1.0

LIFESAVER®

How to install a new LIFESAVER® cube™ UF cartridge

1. **Empty** the cube™ of water and release pressure by unscrewing pump cap.

2. **Unscrew** and remove tap cap and tap.

3. **Remove** the old cartridge and discard it responsibly along with the “O” rings.

4. **Clean** the LIFESAVER® cube™ and pump completely by washing it with mild washing up liquid in warm water (*use a soft cloth for this*). Ensure that all dirt is removed and the cube™ is thoroughly clean. Rinse thoroughly and allow to dry.

5. **Remove** the new LIFESAVER® cube™ UF cartridge from it’s packaging.

6. **Insert** the new cartridge complete with new “O” rings into the cube™ and press down.

7. **Thread** tap cap onto the cube™. Ensure that the tap cap is tightened firmly with the tap pointing straight forward.

8. **Prime** the cartridge (*please follow instructions for the first use shown on the reverse of this guide*).

9. **Ready** to use your LIFESAVER® cube™ again (*please follow instructions for routine use shown on the reverse of this guide*).

Caution! When replacing the LIFESAVER® filter cartridge, the “O” rings positioned above and below the filter must be renewed. Ensure “O” rings are positioned correctly tight against the flange of the filter and are not pinched during reassembly.

The full technical instruction booklet can be found online at www.lifesaversystems.com.

LIFESAVER® systems ltd, Hall Chase, London Road, Marks Tey, Colchester, Essex CO6 1EH UK
t +44(0)1206 580999 f +44(0)1206 215679 e info@lifesaversystems.com
w www.lifesaversystems.com